Presentation Title: Safe Yield Update

Date of Presentation: 12 October 2010

Presented by:

Anne Carroll

Department of Conservation and

Recreation

The following presentation is offered for discussion purposes only and does not necessarily represent current statute, regulation, or policy positions of the Commonwealth of Massachusetts unless specifically acknowledged.

This presentation is not to be cited as a reference. It's purpose is to foster open and broad discussion of the issues as well as help assure public awareness of the discussions as of the date of the presentation.

SUSTAINABLE WATER MANAGEMENT INITIATIVE


SAFE YIELD UPDATE EEA SWMI TECHNICAL SUBCOMMITTEE

Components of Safe Yield

- Basin Yield, Drought/probable driest period (BY)
- Environmental Protection Factor (EPF)
- Storage Volume (S)
- Other Considerations:
 - Time and Space
 - Alternatives where no SYE calculations
 - Consumptive Use

Basin Yield Options

- Option 1: Monthly Q90, annualized
- Option 2: Minimum Year in period of record (recurrence range <Q75 to Q90)
- Option 3: Monthly Q80, annualized




Environmental Protection Factor

- □ Use 25% of August Median Flow (AMF) as target for Safe Yield, therefore 75% August Median flow for EPF
- Translates to 30% loss of fluvial density
- Determine portion of August Basin Yield equal to fraction that represents 25% of August Median (for Ipswich and Charles, ~50%)
- Apply percentage to other months
- Consider using lower percentages in non-summer months

Environmental Protection Factor: Example

Charles River Basin Basin Yield = Monthly Q90's Monthly Allocatable portion = 25% Aug Med / Aug Q90 = 52%



Environmental Protection Factor: Example

Column/							
Row	Α	В	С	D	Е	F	G
			25% of				
		August	August	August	% of August Q90	% of August Q90	% of August
		Median	Median*	Q90	that equals 25% of	that can be taken	Q90 remaining
1	Basin	(cfsm)	(cfsm)	(cfsm)	August Median	for Safe Yield	for EPF
2	Basin A	0.3	0.08	0.15	50%	50%	50%
3	Basin B	0.2	0.05	0.15	33%	33%	67%
4	Basin C	0.5	0.13	0.15	83%	83%	17%
	*Assumes 25% of Aug Median can be taken for Safe Yield, 75% of Aug Median reserved for EPF						

May need a cap on percentage to avoid Basin C situation

Storage Volume

DRAFT Storage Volumes

(for systems that can store more than one year of basin yield and system use)

□ Chicopee 2	250.2
--------------	-------

1	N I I	1 1 1
	Nashua	141.6

□ Westfield 62.6

□ Boston Harbor 1.6

□ Housatonic 0.12

□ Quinebaug 0.07

Consideration of Reservoir Releases

 Releases are most appropriately discussed under criteria/goals, not as part of the storage methodology


Time and Space: Scale

Use
"administrative"
split where
basins are
geographically
separated and
don't flow into
each other:

Boston Harbor

South Coastal

Hudson



Calculating Basin Yield for non-SYE Basins

For Buzzards Bay, Cape Cod, Islands, Narragansett-Mt. Hope, North Coastal, and South Coastal

Continue to evaluate 3 options:

- Use most similar basin and apply its basin yield (mgd/mi2)
- Use data in SYE for Cape & Islands and Plymouth Carver Aquifer
- Evaluate recharge numbers from DEP's October
 2009 proposal

Consumptive Use: components

- Returns that could be considered:
 - Septic Returns
 - Groundwater Discharges
 - Surface Water Discharges
- Removals that could be considered:
 - Public withdrawals
 - Private well withdrawals
 - Infiltration and Inflow

Consumptive Use: pros and cons

- □ Pros:
 - Giving credit/accounting for returns
 - Giving credit for keeping water local
- □ Cons:
 - Water Quality concerns
 - Data Quality concerns
 - Don't have a method for I/I estimate
- Site specific consideration during allocation may be most appropriate